



CONTRACT CONTRACTOR SERVING DESCRIPTION

AD-A176 392

UNCLASSIFIED SECURITY CLASSIFICATION OF THIS PAGE FOR REPRODUCTION PURPOSES (



REPORT DOCUMENTATION PAGE					
18 REPORT SECURITY CLASSIFICATION Unclassified	OTIC	16 RESTRICTIVE	MARKINGS		
2a. SECURITY CLASSIFICATION AUTHOR	3 DISTRIBUTION/AVAILABILITY OF REPORT				
26. DECLASSIFICATION / DOWNGRADING THEOD	Approved for public release;				
	distribution unlimited.				
4. PERFORMING ORGANIZATION REPO MBER(S) 5. MC			MUNITORING ORGANIZATION REPORT NUMBER(S)		
	D^{*}		ARO 19572.4	1-FC-S	
6a. NAME OF PERFORMING ORGANIZATION 6b. OFFICE STMBOL		7a. NAME OF MONITORING ORGANIZATION			
DCW Industries (If applicable)					
	U. S. Army Research Office				
6c. ADDRESS (City, State, and ZIP Code)	7b. ADDRESS (City, State, and ZIP Code)				
La Canada, CA 91011	P. O. Box 12211				
	Research Triangle Park, NC 27709-2211				
8a. NAME OF FUNDING/SPONSORING ORGANIZATION	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER				
U. S. Army Research Office	(If applicable)	DAAG29-83-C-0003			
Bc ADDRESS (City, State, and ZIP Code)		10 SOURCE OF FUNDING NUMBERS			
P. O. Box 12211		PROGRAM	PROJECT	TASK	WORK UNIT
Research Triangle Park, NC 27	7709-2211	ELEMENT NO.	NO.	NO.	ACCESSION NO
11 TITLE (Include Security Classification)					
Development of a Complete Model of Turbulence Revisited					
12 PERSONAL AUTHOR(S)					
David C. Wilcox 13b TIME COVERED 14. DATE OF REPORT (Year, Month, Day) 15 PAGE COUNT					
Final FROM 12	December		ay) 13 P	4	
16 SUPPLEMENTARY NOTATION					
The view, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position.					
of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation. 17 COSATI CODES 18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)					
FIELD GROUP SUB-GROUP	Unsteady Boundary Layers				
	Engineer Revnolds	Engineering Applications, Turbulence Model Equations Reynolds Stress, Boundary Layers			
19 ABSTRALT (Continue on reverse if necessary and identify by block number)					
A CONTINUE OF TEVERSE IT NECESSARY AND IDENTITY BY DIOCK HUMBER)					
The primary technical objective of this research project has been					
to develop and test a new set of constitutive equations suitable					
for general engineering applications. In accomplishing this					
objective, particular emphasis has been focused upon predicting rates of departure from and return to equilibrium. Throughout					
the research in this project, a secondary goal has been to devise					
our turbulence model equations subject to the self-imposed con-					
our turbulence model equations subject to the self-imposed con- straints that the resulting equations pose no special difficul- ties for conventional numerical procedures, and, to the greatest					
extent possible, reflect much more of the physics of turbulence					
than previously attempted in an engineering model.					
20 DISTRICT ASSISTED AND ASSISTED ASSISTED AND ASSISTED ASSISTED AND ASSISTED ASSISTED AND ASSISTED AND ASSISTED AND ASSISTED ASSISTED AND ASSISTED A					
☐ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT ☐ DTIC USERS ☐ Unclassified 22a NAME OF RESPONSIBLE INDIVIDUAL 22b TELEPHONE (Include Area Code) 22c OFFICE SYMBOL					
The same of the same and the sa				L OFFIC	CC FINITOT

DEVELOPMENT OF A COMPLETE MODEL OF TURBULENCE REVISITED

bу

David C. Wilcox

December 1986

Contract DAAG-29-83-0003

Final Report Number DCW-P-29-02

Accesion For

NTIS CRA&I
DTIC TAB
Unannounced
Justification

By
Dist ibution/
Availability Codes

Dist Avail and/or
Special

Prepared for

U.S. ARMY RESEARCH ORGANIZATION
Research Triangle Park, North Carolina



DCW INDUSTRIES, INC.
5354 Palm Drive
La Cañada, California 91011
818/790-3844

1. OVERVIEW OF WORK ACCOMPLISHED

The primary technical objective of this research project has been to develop and test a new set of constitutive equations suitable for general engineering applications. In accomplishing this objective, particular emphasis has been focused upon predicting rates of departure from and return to equilibrium. Throughout the research in this project, a secondary goal has been to devise our turbulence model equations subject to the self-imposed constraints that the resulting equations pose no special difficulties for conventional numerical procedures, and, to the greatest extent possible, reflect much more of the physics of turbulence than previously attempted in an engineering model.

These primary objectives have been accomplished in this project in three distinct phases. The first phase focused on reassessing two-equation turbulence models and postulating a Phase One was accomplished in the first year of Contract DAAG-29-83-C-0003. The second phase concentrated upon removing the usual turbulence model assumption that Reynolds proportional to mean strain rate. Removing this assumption was accomplished by postulating a new model known as the multiscale model. Phase Two was accomplished in Year's Two and Three of the The third phase was dedicated to applying the Contract. multiscale model to unsteady boundary layers. Phase Three conducted during the fourth and final year of this Contract.

1.1 Phase One (Year One)

During the first year our progress was very rapid. By applying asymptotic methods to the defect layer with adverse pressure gradient, we found very quickly that existing models were obviously going to be inaccurate for boundary layers subjected to adverse pressure gradient. We found that a simple change in dependent variables yields a turbulence model with greatly improved predictive accuracy for such boundary layers. A wide range of numerical applications to attached two-dimensional boundary layers confirmed our asymptotic analysis and thus completed the first step of our overall research plan. Complete details of the first year's research efforts were published as an AIAA paper in January, 1984, viz,

Wilcox, D.C., "A Complete Model of Turbulence Revisited," AIAA Paper 84-0176 (1984).

1.2 Phase Two (Years Two and Three)

The second step proved far more difficult and, in fact, involved several false starts. Three different approaches were implemented, all of which ultimately were discarded for various reasons. A full year of research was invested in finding out what not to do. As with all such research, the effort was not fruitless. Each approach improved upon the preceding attempt, and finally formulation number four satisfied the original objective.

The ultimate model developed is now referred to as the multiscale that is derived from the fart The name two distinct energy scales are used to describe the turbulence, "small" eddies and one for "large" eddies. Selection of this type of description satisfies another of our original objectives, to incorporate much more of the physics of turbulence During the third year, the model than previously attempted. were able to demonstrate that the model accurately describes properties of homogeneous turbulence and two-dimensional boundary with adverse pressure gradient for both compressible incompressible flow conditions. Complete details of the second and third year's research efforts were published as an AIAA paper in January, 1986, viz,

Wilcox, D.C., "Multiscale Model for Turbulent Flows," AIAA Paper 86-0029 (Jan 1986).

1.3 Phase Three (Year Four)

THE PROPERTY SECTIONS AND PARTY OF THE PROPERTY OF THE PROPERT

In our fourth and final year of Contract DAAG29-83-C-0003 we have extended application of the multiscale model to more complex flows. The applications include three Mach 3 shock-separated turbulent boundary layers and a total of nine unsteady turbulent boundary layer computations for a nontrivial range of Strouhal numbers.

Although only a cursory examination of model predictions separated flows was made, our Navier-Stokes computations produced potentially profound results. We performed Navier-Stokes computations only as an intermediate step toward developing an unsteady boundary layer program. In testing the program, simulated the flow attending reflection of an oblique shock from We first performed the computation with the twoa flat plate. equation model developed in the first year's research activities. Results were satisfactory with a steady solution naturally in time. Then, we repeated the computation with the multiscale model and a provocative thing happened. with most experimental observations, the flow within and in the wake of the separation bubble was found to be inherently unsteady.

Our unsteady boundary-layer computations offer the first definitive measure of how accurately the multiscale model simulates the physics of turbulent boundary layers. For a wide range of Strouhal numbers, we have more-or-less duplicated the structure of a turbulent boundary layer subjected to a sinusoidally varying adverse pressure gradient. Our two-equation model is far less accurate for these flows. Complete details of the fourth year's research efforts will be published as an AIAA paper in January, 1987, viz,

D.C. Wilcox, "Advanced Applications of the Multiscale Model for Turbulent Flows," AIAA Paper 87-0290 (Jan 1987).

1.4 Concluding Remarks

CONTRACTOR DESCRIPTION BUILDING SESSIONES SESSIONES PROFIZE PERFERENT DESCRIPTION RESESSION ASSASSION IN LOS

As a final comment on the results of our research efforts under Contract DAAG29-83-C-0003 relative to the original objectives, we feel completely justified in claiming that our goal of constructing a "numerically well behaved" model has been accomplished. To justify this claim, we include Table 1 which shows the computing-time increase relative to the two-equation model for four different types of computational procedures.

Table 1. Computing time comparison.

Type of	Percent Increase			
Application	over 2-Equation Model			
2-D Boundary Layer	25%			
3-D Boundary Layer	40%			
Navier Stokes	45%			
Unsteady Boundary Layer	45%			

2. TECHNOLOGY TRANSFER

Working copies of the two-dimensional/axisymmetric boundary-layer program, EDDYBL, which embodies the multiscale and $k-\omega$ two-equation models developed under Contract DAAG-29-83-C-0003 have been installed at the following facilities.

ACA Industries, Inc. Air Force Office of Scientific Research Ballistic Research Laboratory BMO/MYES (Norton Air Force Base) Carleton University NASA Ames Research Center NASA Langley Research Center North Carolina Agricultural and Technical State University Office of Naval Research Physical Research, Inc. Redstone Arsenal Rutgers University Stanford University University of California, Los Angeles University of New Mexico University of Tennessee, Knoxville University of Tennessee Space Institute

boom booksees seeksees the books